

coming up

- β due Thursday, November 14, at noon
 - in-class presentations Nov 14
- PEaRCE online activity due tomorrow
- No UMass classes Tuesday Nov 5 – GO VOTE
- First team assessment, due November 7
 - <https://forms.gle/1SKoMFJn2yrMhVpw8>

1

Testing

2

Real programmers need no testing!

- 5) I want to get this done fast, testing is going to slow me down.
- 4) I started programming when I was 2. Don't insult me by testing my perfect code!
- 3) Testing is for incompetent programmers who cannot hack.
- 2) We are not UConn students, our code actually works!
- 1) "Most of the functions in Graph.java, as implemented, are one or two line functions that rely solely upon functions in HashMap or HashSet. I am assuming that these functions work perfectly, and thus there is really no need to test them."
 - *an excerpt from a student's e-mail*


3

Software (not) testing in action

https://www.youtube.com/watch?v=PK_yguLapgA

4

Ariane 5 rocket



- The rocket self-destructed 37 seconds after launch
- Reason: A control software bug that went undetected
 - Conversion from 64-bit floating point to 16-bit signed integer value had caused an exception
 - The floating point number was larger than 32767 (max 16-bit signed integer)
 - Efficiency considerations had led to the disabling of the exception handler.
 - Program crashed → rocket crashed
- Total Cost: over \$1 billion


5

Therac-25 radiation therapy machine

- Caused excessive radiation, **killing patients** from radiation poisoning
- What happened?
 - Updated design had removed hardware interlocks that prevent the electron-beam from operating in its high-energy mode. Now all the safety checks are done in the software.
 - The software set a flag variable by incrementing it. Occasionally an arithmetic overflow occurred, causing the software to bypass safety checks.
 - The equipment control task did not properly synchronize with the operator interface task, so that race conditions occurred if the operator changed the setup too quickly.
 - This was evidently missed during testing, since it took some practice before operators were able to work quickly enough for the problem to occur.

6

Mars Polar Lander



- Sensor signal falsely indicated that the craft had touched down when it was 130-feet above the surface.
 - the descent engines to shut down prematurely
- The error was traced to a single bad line of software code.
- NASA investigation panels blame for the lander's failure, "are well known as difficult parts of the software-engineering process,"

7

Testing is for every system

- Examples showed particularly costly errors
- But every little error adds up
- Insufficient software testing costs **\$22-60 billion** per year in the U.S. [NIST Planning Report 02-3, 2002]
- If your software is worth writing, it's worth writing right

8

Building quality software

- What Impacts the Software Quality?
- External
 - Correctness *Does it do what it suppose to do?*
 - Reliability *Does it do it accurately all the time?*
 - Efficiency *Does it do with minimum use of resources?*
 - Integrity *Is it secure?*
- Internal
 - Portability *Can I use it under different conditions?*
 - Maintainability *Can I fix it?*
 - Flexibility *Can I change it or extend it or reuse it?*
- Quality Assurance
 - The process of uncovering problems and improving the quality of software.
 - Testing is a major part of QA.

9

The phases of testing

- Unit Testing
 - Is each module does what it suppose to do?
- Integration Testing
 - Do you get the expected results when the parts are put together?
- Validation Testing
 - Does the program satisfy the requirements
- System Testing
 - Does it work within the overall system

10

Unit Testing

- A test is at the level of a method/class/interface
Check that the implementation matches the specification.
- Black box testing
 - Choose test data *without* looking at implementation
- Glass box (white box) testing
 - Choose test data *with* knowledge of implementation

11

How is testing done?

Basic steps of a test

- 1) Choose input data / configuration
- 2) Define the expected outcome
- 3) Run program / method against the input and record the results
- 4) Examine results against the expected outcome

12


What's so hard about testing ?

- "just try it and see if it works..."
- ```
int procl(int x, int y, int z)
// requires: 1 <= x,y,z <= 1000
// effects: computes some f(x,y,z)
```
- Exhaustive testing would require 1 billion runs!
  - Sounds totally impractical
- Could see how input set size would get MUCH bigger
- Key problem: **choosing test suite (set of partitions of inputs)**
  - Small enough to finish quickly
  - Large enough to validate the program

13

## Approach: partition the input space

- Input space very large, program small
  - behavior is the "same" for sets of inputs
- Ideal test suite:
  - Identify sets with same behavior
  - Try one input from each set
- Two problems
  - 1. Notion of **the same behavior** is subtle
    - Naive approach: **execution equivalence**
    - Better approach: **revealing subdomains**
  - 2. Discovering the sets requires perfect knowledge
    - Use heuristics to approximate cheaply



14

## Naive approach: execution equivalence

```
int abs(int x) {
// returns: x < 0 => returns -x
// otherwise => returns x

if (x < 0) return -x;
else return x;
}
```

All  $x < 0$  are **execution equivalent**:  
program takes same sequence of steps for any  $x < 0$

All  $x \geq 0$  are execution equivalent

Suggests that  $\{-3, 3\}$ , for example, is a good test suite

15

## Why execution equivalence doesn't work

Consider the following buggy code:

```
int abs(int x) {
// returns: x < 0 => returns -x
// otherwise => returns x

if (x < -2) return -x;
else return x;
}
```

**$\{-3, 3\}$  does not reveal the error!**

Two executions:

$x < -2$        $x \geq -2$

Three behaviors:

$x < -2$  (OK)     $x = -2$  or  $-1$  (bad)     $x \geq 0$  (OK)

16

## Revealing subdomain approach

- "Same" behavior depends on specification
- Say that program has "same behavior" on two inputs if
  - 1) gives correct result on both, or
  - 2) gives incorrect result on both
- Subdomain is a subset of possible inputs
- Subdomain is **revealing** for an error, E, if
  - 1) Each element has **same behavior**
  - 2) If program has error E, it is revealed by test
- Trick is to divide possible inputs into sets of revealing subdomains for various errors

17

## Example

- For buggy abs, what are revealing subdomains?

```
- int abs(int x) {
 if (x < -2) return -x;
 else return x;
- }
```

**$\{-1\}$   $\{-2\}$   $\{-2, -1\}$   $\{-3, -2, -1\}$**

**$\{-2, -1\}$**

- Which is best?

18

## Heuristics for designing test suites

- A good heuristic gives:
  - few subdomains
  - $\forall$  errors  $e$  in some class of errors  $E$ ,  
high probability that some subdomain is revealing for  $e$
- Different heuristics target different classes of errors
  - In practice, combine multiple heuristics

19

## Black-box testing

- Heuristic: explore alternate paths through specification  
the interface is a **black box**; internals are hidden
- Example
  - `int max(int a, int b)`

```
// effects: a > b => returns a
// a < b => returns b
// a = b => returns a
```
  - 3 paths, so 3 test cases:
    - (4, 3) => 4 (i.e., any input in the subdomain  $a > b$ )
    - (3, 4) => 4 (i.e., any input in the subdomain  $a < b$ )
    - (3, 3) => 3 (i.e., any input in the subdomain  $a = b$ )

20

## Black-box testing: advantages

- Process not influenced by component being tested
  - Assumptions embodied in code not propagated to test data.
- Robust with respect to changes in implementation
  - Test data need not be changed when code is changed
- Allows for independent testers
  - Testers need not be familiar with code

21

## A more complex example


- Write test cases based on paths through the specification
  - `int find(int[] a, int value) throws Missing`

```
// returns: the smallest i such
// that a[i] == value
// throws: Missing if value not in a[]
```
  - Two obvious tests:
    - ( [4, 5, 6], 5 ) => 1
    - ( [4, 5, 6], 7 ) => throw Missing
  - Have I captured all the paths?  
( [4, 5, 5], 5 ) => 1
  - Must hunt for multiple cases in effects or requires

22

## Heuristic: boundary testing

- Create tests at the edges of subdomains
- Why do this?
  - off-by-one bugs
  - forget to handle empty container
  - overflow errors in arithmetic
  - program does not handle aliasing of objects
- Small subdomains at the edges of the “main” subdomains have a high probability of revealing these common errors



23

## Common boundary cases

- Arithmetic
  - Smallest/largest values
  - Zero
- Objects
  - Null
  - Circular
  - Same object passed to multiple arguments (aliasing)

25

## Boundary cases: arithmetic overflow

- `public int abs(int x)`
- `// returns: |x|`
- Tests for abs
  - what are some values or ranges of x that might be worth probing?
    - $x < 0$  (flips sign) or  $x \geq 0$  (returns unchanged)
    - around  $x = 0$  (boundary condition)
    - Specific tests: say  $x = -1, 0, 1$
- How about...
  - `int x = -2147483648; // this is Integer.MIN_VALUE`  
`System.out.println(x < 0); // true`  
`System.out.println(Math.abs(x) < 0); // also true!`
- From Javadoc for `Math.abs`:
  - Note that if the argument is equal to the value of `Integer.MIN_VALUE`, the most negative representable int value, the result is that same value, which is negative

26

## Boundary cases: duplicates and aliases

```
<E> void appendList(List<E> src, List<E> dest) {
// modifies: src, dest
// effects: removes all elements of src and
// appends them in reverse order to
// the end of dest
//
//
while (src.size() > 0) {
 E elt = src.remove(src.size() - 1);
 dest.add(elt);
}
}
```

What happens if `src` and `dest` refer to the same thing?

- Aliasing (shared references) is often forgotten

27

## Clear (glass, white)-box testing

- Goals:
  - Ensure test suite covers (executes) all of the program
  - Measure quality of test suite with % coverage
- Assumption:
  - High coverage →
  - (no errors in test output → few mistakes in program)
- Focus: features not described by specification
  - Control-flow details
  - Performance optimizations
  - Alternate algorithms for different cases

28

## Glass-box motivation

There are some subdomains that black-box testing won't catch:

```
boolean[] primeTable = new boolean[CACHE_SIZE];
boolean isPrime(int x) {
 if (x > CACHE_SIZE) {
 for (int i=2; i<x/2; i++) {
 if (x%i==0) return false;
 }
 return true;
 } else {
 return primeTable[x];
 }
}
```

Important transition around  $x = \text{CACHE\_SIZE}$

29

## Glass-box testing: advantages

- Insight into test cases
  - Which are likely to yield new information
- Finds an important class of boundaries
  - Consider `CACHE_SIZE` in `isPrime` example
- Need to check numbers on each side of `CACHE_SIZE`
  - `CACHE_SIZE-1`, `CACHE_SIZE`, `CACHE_SIZE+1`
- If `CACHE_SIZE` is mutable, we may need to test with different `CACHE_SIZE`'s

30

## Glass-box challenges

- Definition of **all of the program**
  - What needs to be covered?
  - Options:
    - Statement coverage
    - Decision coverage
    - Loop coverage
    - Condition/Decision coverage
    - Path-complete coverage
- 100% coverage not always reasonable target

increasing  
number of  
cases  
(more or less)

100% may be unattainable (dead code)  
High cost to approach the limit

31

## Regression testing

- Whenever you find a bug
  - Reproduce it (before you fix it!)
  - Store input that elicited that bug
  - Store correct output
  - Put into test suite
  - Then, fix it and verify the fix
- Why is this a good idea?
  - Helps to populate test suite with good tests
  - Protects against regressions that reintroduce bug
    - It happened once, so it might again

32

## Rules of Testing

- First rule of testing: ***Do it early and do it often***  
 Best to catch bugs soon, before they have a chance to hide.  
 Automate the process if you can  
 Regression testing will save time.
- Second rule of testing: ***Be systematic***  
 If you randomly thrash, bugs will hide in the corner until you're gone  
 Writing tests is a good way to understand the spec  
 Think about revealing domains and boundary cases  
 If the spec is confusing → write more tests  
 Spec can be buggy too  
 Incorrect, incomplete, ambiguous, and missing corner cases  
 When you find a bug → fix it first and then write a test for it

33

## Testing summary

- Testing matters
  - You need to convince others that module works
- Catch problems earlier
  - Bugs become obscure beyond the unit they occur in
- Don't confuse volume with quality of test data
  - Can lose relevant cases in mass of irrelevant ones
  - Look for revealing subdomains ("characteristic tests")
- Choose test data to cover
  - Specification (black box testing)
  - Code (glass box testing)
- Testing can't generally prove absence of bugs
  - But it can increase quality and confidence

34